


Multi Mono Specialised



DESERV™

*Module images for representation purpose only

Solar PV Module DESERV 3M6 or 3M6H

60 Cells: 260 Wp - 275 Wp

72 Cells: 315 Wp - 335 Wp

The ideal PV Module for all applications that use the highest quality of PV Cells, in-house Encapsulants, and Backsheets.

*60 cells (250 Wp, 255 Wp), 72 cells (300 Wp, 305 Wp, 310 Wp) available on request

Certifications:

- IEC Certified: 61215, 61730
- IEC TS 62804, 61853
- IEC 61701
- IEC 62716
- IEC 60068-2-68
- CAN/CSA: 61730
- UL Certified 1703
- DEWA Listed
- BIS Number R-63000760
- MCS Approved
- Independently audited by SOLARBUYER
- IMS Certified Company - ISO 9001: 2015 & OHSAS 18001:2007
- EMS - ISO 14001: 2015



SAFE



IP67 Junction box



10 years of product warranty



25 Years of limited power output warranty



1000 Vdc or 1500 Vdc



RELIABLE



Extreme weather resilience



Windspeed - 2400 Pa,
Snowload - 5400 Pa



Highly reliable anti-reflective
coated glass



HIGH PERFORMANCE



PID resistant



Low light performance



High power density

Ideal for:



Residential



Commercial



Utility



Off-grid

Registered Office

98, Jolly Maker Chambers No.2,
225 Nariman Point,
Mumbai - 400 021,
Maharashtra, India

Factory

Plot No.6, Survey # 114/P,
Srinagar Village, Maheshwaram
Mandal, Dist - Rangareddy,
Hyderabad - 501 359, Telangana, India

- Please refer to the installation manual for detailed information.

Performance under standard test conditions (1000w/m², AM 1.5, 25 °C)

DESERV 3M6 or 3M6H (Wp)	60 Cells				72 Cells				
	260	265	270	275	315	320	325	330	335
Rated power (Pmax), Wp	260	265	270	275	315	320	325	330	335
Max. power voltage (Vmp), V	30.72	30.77	30.95	31.16	36.92	37.20	37.41	37.67	37.90
Max. power current (Imp), A	08.48	08.64	08.74	08.84	08.56	08.62	08.70	08.79	08.85
Open circuit voltage (Voc), V	38.40	38.46	38.70	38.97	46.15	46.18	46.21	46.24	46.27
Short circuit current (Isc), A	08.83	09.00	09.13	09.14	08.92	09.07	09.19	09.31	09.41
Module efficiency (%)	16.05	16.36	16.67	16.97	16.29	16.55	16.81	17.07	17.33
NOCT (Wp) at 45 ±2 °C @800 W/m²									
Pmax (W)	193.50	197.22	200.94	204.66	234.43	238.15	241.87	245.59	249.31
Max. power voltage (Vmp), V	28.09	28.14	28.30	28.49	33.76	34.02	34.21	34.45	34.66
Max. power current (Imp), A	06.90	07.03	07.11	07.19	06.97	07.01	07.08	07.15	07.20
Open circuit voltage (Voc), V	35.70	35.76	35.98	36.23	42.91	42.93	42.96	42.99	43.02
Short circuit current (Isc), A	07.21	07.35	07.46	07.47	07.29	07.41	07.51	07.60	07.69

Mechanical Characteristics	60 & 72
Cable	No. 12 AWG, 4mm ² , (1.2m Standard)
PV Connectors	MC4 Compatible (MC4/TYCO on request)
Frame	Anodized Aluminum Alloy
Junction box	IP67 Junction box with 4 rail (3 bypass diodes of 15 A)
Glass	3.2mm Thick low iron tempered (4mm available on request)

Operating Conditions	60 & 72
Ambient temperature, °C	-40 to +85
Max. system voltage, Vdc	1000 or 1500
Hail impact velocity, m/sec	23
Max. surface load capacity, Pa	5400
Max. wind speed capacity, Pa	2400

Cell Temperature Coefficient	60 & 72
Open circuit voltage	-0.30 % / °C
Short circuit current	+0.05 % / °C
Nominal power	-0.40 % / °C

Physical Parameters	260 Wp - 275 Wp	315 Wp - 335 Wp
No. of cells	60	72
Module dimension (mm)	1641 X 987 (± 2)	1958 X 987 (± 2)
Module thickness (mm)	40 or 35	40 or 35
Approximate weight (kg)	18 or 17.7	21.5 or 21.2
Packaging Configuration - 3M6		
	60	72
No. of Modules/pallet	26 or 29	26 or 29

Module Dimension Diagrams (mm)

