

Mono Crystalline Silicon Modules



3S6- 275/280/285/290/295/300

DESERV 3S6 - 60 cells, Photovoltaic Mono Module Series is offered with power ratings ranging from 275 Wp to 300 Wp. These high performance Mono-Crystalline Silicon Modules are designed for on-grid, as well as off-grid applications.

KEY FEATURES



Made in India



Positive power tolerance



Highly reliable anti- reflective coated glass



Windspeed - 2400 Pa
Snowload - 5400 Pa



IP67 Junction box



1000 V V_{dc}




PID resistant



Limited power output warranty



Product warranty



Independently Audited by



IEC Certified - 61215, 61730

IMS Certified Company (ISO 9001:2015 & OHSAS 18001:2007)

RenewSys has a global presence with offices in Dubai, Johannesburg, Lagos, London, Mauritius and Singapore, as well as representative offices in USA and many countries of Europe.



CONSERV®
E 360 - POE
Encapsulant

Performance under standard test conditions (1000W/m² AM 1.5, 25°C)

	DESERV 3S6 - 275	DESERV 3S6 - 280	DESERV 3S6 - 285	DESERV 3S6 - 290	DESERV 3S6 - 295	DESERV 3S6 - 300
Rated power (Pmax), Wp	275	280	285	290	295	300
Open circuit voltage (Voc), V	38.9	39.1	39.42	39.62	39.65	39.8
Short circuit current (Isc), A	9.31	9.42	9.49	9.55	9.67	9.7
Max power voltage (Vmp), V	32.5	32.7	32.8	32.85	33.05	33.4
Max power current (Imp), A	8.48	8.59	8.70	8.84	8.93	8.99
Module efficiency (%)	16.94	17.25	17.55	17.86	18.17	18.48

Operating Conditions

Ambient temperature, °C	-40 to + 85
Maximum system voltage, Vdc	1000
Hail impact velocity, m/sec	23
Maximum surface load capacity, Pascals	5400

Cell Temperature Coefficients

Open circuit voltage	- 0.32 % / °C
Short circuit current	+ 0.049 % / °C
Nominal power	- 0.41 % / °C

Physical Parameters

No. of cells	60
Module dimensions (mm)	1640 X 987 or 990
Module thickness (mm)	40
Approximate weight (kg)	18

Mechanical Characteristics

Cable	NO. 12 AWG, 4mm ²
PV connectors	MC4/MC4 (Compatible)
Frame	Anodized Aluminum Alloy
Junction box	IP67 Junction Box With 4 Rail
Glass	3.2mm Thick Low Iron Tempered

NOCT


	275 Wp	280 Wp	285 Wp	290 Wp	295 Wp	300 Wp
Rated power (Pmax), Wp	204.66	208.38	212.11	215.83	219.55	223.27
Open circuit voltage (Voc), V	29.72	29.91	30.00	30.04	30.23	30.55
Short circuit current (Isc), A	6.90	6.99	7.08	7.20	7.27	7.32
Max power voltage (Vmp), V	36.17	36.36	36.65	36.84	36.87	37.01
Max power current (Imp), A	7.61	7.70	7.75	7.80	7.90	7.92

Registered Office


98, Jolly Maker Chambers No.2, 225 Nariman Point, Mumbai - 400 021, Maharashtra, India
Tel.: + 91 22 30040500

Factory

Plot No.6, Survey # 114/P, Srinagar Village, Maheshwaram Mandal, Dist-Rangareddy, Hyderabad - 501 359, Telangana, India
Tel.: + 91 40 67303000 Fax: + 91 40 67303003



RenewSys DESERV 3S6 - 300 Wp



RenewSys DESERV 3S6 - 300 Wp

